

## **Dirko Elring vloeibare pakking 70ml grijs**

---

Dé vloeibare pakking voor de proffesionele motorbouwers! Voor als het echt dicht moet zijn en blijven!

Dit is de meest gebruikte pakkingsoort voor de bijna alle toepassingen. (o.a. als carterpakking, versnellingsbakpakking, enz.)

In 70ml tube incl. alle toebehoren.

### **Inhoud:**

**Dirko grijs 70 ml -50°C ... +180°C**

### **Extra informatie:**

The permanently elastic, temperature-resistant, siliconbased, universal sealing compound.

Temperature stability: -50°C to +180°C

This extremely versatile, high-strength sealing compound seals surfaces, gaps and cracks reliably, even where there is movement.

Dirko's viscosity and absolutely permanent elasticity rapidly stop leakage of oil, water and air. Even structural parts with hairline cracks are made functional again within minutes. Dirko is resistant to ozone, sunlight, extreme weather conditions, hot and

cold water, seawater, greases, mineral oils (also with additives), aliphatic hydrocarbons, detergents and numerous chemicals.

These advantages make Dirko equally suitable for use on its own, as a sealant applied from the exterior between surfaces without disassembly, or in combination with flat gaskets.

### **Application**

Carefully remove any existing sealant residues using a plastic spatula. Clean and degrease the sealing surfaces. Apply

Dirko. Skin formation time: approx. 5 – 10 minutes. "Wet-in-wet" assembly, i. e. the parts are joined immediately before a skin begins to form, ensures instant sealing.

Processing temperature: +5°C to +30°C.